

# VSB Modulator

AS 606



Sharp Vision VSB Modulators AS 606 are more suitable for small control room having 36 or less channels. It uses stable and crystal control circuit to deliver good picture & sound quality. They are economical in price.



## Features:

- 19 Inch Rack Mounted
- Any Fixed Ch from E2 ~ S20 (36 Channels)
- Adj. Ch. Interference >70dBC
- Stable Crystal Controlled Frequency
- Loop through AC Power

## Specifications:

- RF O/P Freq Range : PAL B/G {47 ~ 300MHz}
- RF O/P Level : 105 dB $\mu$ V
- RF O/P Level Range : 20 dB Adjustable
- Frequency Stability :  $\pm$  10 KHz
- Output Impedance : 75 ohms
- Video I/P Level : 1.0 Vp-p for 87.5% Modulation
- Video I/P Impedance : 75 ohms
- Audio I/P Impedance : 600 Ohms – Unbalance
- Audio Input Level : 500 mV p-p
- Mains Power : 220 VAC  $\pm$  10%, 50 Hz



An International Quality Product from **ANALOG SYSTEMS**

**website:** [www.sharpvisiononline.in](http://www.sharpvisiononline.in)

**Email:** [sales@sharpvisiononline.in](mailto:sales@sharpvisiononline.in) / [analogsystems@vsnl.net](mailto:analogsystems@vsnl.net)